




OFFICE MODULES & SUSPENDED
LUMINAIRES

advanced systems



PERSCARA RX/XS
TECHNICAL SPECIFICATION DATA

Strategic Lighting Group | Strategic Lighting (Europe) Limited | Narrow Lane End Works, 64 Worple Road, Epsom, Surrey KT18 7AG | England UK
Tel. +44 (0)845 241 4631 | Fax. +44 (0)845 241 4632 | Email. info@strategiclighting.com | www.strategiclighting.com



GIOTTO XS

fluorescent -dimmable

IP20



32

- Energy Saving Technology
- Green Energy Technology
- Lamp Type Technology
- Wattage - Unit
2 x 24W dimmable + spotlights
- Voltage
ac - alternating current only
- Integral HF Ballast
- Lumens / Watt
value - based on 24W at 1750lms
- CRI - Group Index
value - 80 - 90%
- IP Rating
Standard Interior Only
- Insulation Class
- Functional Earth Required
- Product Weight
Kilograms/unit - excluding spots
- ENEC compliance
- CE mark
- F - mark
fire safe rating
- Environmental Technology

Product Purpose & Meaning

- The Giotto XS products provides clean lines with the use of optional discreet built in spotlights. This minimises lighting points, reduces install costs, enables wall perimeter lighting, as well as lighting of notice boards, artwork & friezes.
- The name "Giotto XS" [Jott-o] is a tribute to the Italian artist and architect who appreciated the power of light for his "art".

Product Summary

- Flush recessed office direct module with outstanding microprismatic diffuser [using Fluxidrive™ technology] with optional integrated spotlights.
- Optical controller also available in a louvre version.
- Optional adjustable tilting spot /downlights in LED or CDM-T.
- Improved glare control and high output lighting.
- Dimmable

Applications

- Main office lighting, dealer desks, control and operational rooms, wall washing or highlight spotlights.
- School classrooms, friezes and artwork displays.
- Ideal for showrooms and retail.
- Display & exhibitions.

Main Unit Performance

Lamp Type	T5 G5
Lamp Qty	1 or 2
Lamp Source	Philips, Osram or GE.
Lumen Output	refer to manufacturers data
Lamp CRI	> 90
Life	typically 20,000 25,000hrs
Optic Beams	90° [half peak]

Optional Spotlight Performance

LED Option	LED: 19W/20W Philips Fortimo SLM Series
Lamp Type	LED : 1,500lms
Lumen Output	LED > 80
Lamp CRI	LED : 50,000hrs
LED Life	Medium 32° (Half Peak Brightness)
Optic Beams	Monochromatic Whites
LED Colours	- 30°C / +85°C
Working T°C	

Metal Halide Option

Lamp Type	Metal Halide : 20W or 35W / 70W CDM-T
Lumen Output	Metal Halide : 35W - 3,300lms 70W - 6,600lms
Lamp CRI	Metal Halide 84
LED Life	Metal Halide : 12,000hrs
Colours	Metal Halide : 3000K / 4200K

Electrical Data

Voltage	230Vac mains
Load Watts	Variable
Cable Terminal	Yes
Gear	Integrated
Configuration	Mains Power
Dimming	T5 in usual / Spotlights in LED Fortimo only
Data Protocol(s)	DALI, 0-10V, DSI [LED in DALI Touch]

Description

A 600 x 600 modular office luminaire for performance direct component lighting of working spaces. Uses flush closed side paneling with advanced technoprismatic fluxidrive™ light controller diffuser at competitive market pricing. Prismatic Fluxidrive™ technology offers smooth light anti-glare control with volumised light appearance and high output ratios. Alternative light controller in cross-blade cell louvre. Both versions with optional 50° tilt spotlights - as for GLIMA series shown on page 152-153, utilising high output LED with maximum 1500lm high quality superior commercial grade Philips "Fortimo SLM" series LED for ultimate confidence. LED available in optional 3000K-4000K. Full photometrics and calibrated heat sink for reliability. LED designed in medium 34° beam. Alternative LED surface suspended spotlight - "JEWEL" as shown on page 221, as well as metal halide eyeball as for luminaire GLIMA - shown on page 153. Integrated gear on all lamp types. Suitable for lay-in modular T-Bar ceilings in 600x600 plaster board fixings [add post-fix to order code]. Versions for plank and clip-in ceiling tiles on request.

Construction & Finishes

Pressed formed steel & aluminium housing and bezel with LED spotlight units with cast aluminium heat sink. Reflector in high output spun Aluminium. Standard finish in painted white Custom RAL options. Fluxidrive technoprismatic [option in PC to Tpa >850°C]

Main Features

- direct / indirect glare control.
- Fluxidrive technoprismatic [option in PC to Tpa >850°C].
- integrated spotlight options.
- Fluxidrive superior optical controller.

Mounting

- Tensioned Clips for plasterboard type ceilings.
 - No remote gear required.
 - 3 Core Connectors
- Live & Neutral power feeds - with functional Earth

Connection Diagram A

- Connection is for standard main voltage.
- See Connection Diagram A - Page 324.

GIOTTO XS

fluorescent -dimmable



33

Module Only



Prismatic

600 x 600 recessed office module only for central techno-prismatic fluxidrive™ diffuser [micro-prismatic].


GIO.M155.TP	600 x 600 module	1 x 55W TC-L 2G11	Output - 4800lms	Techno-Prismatic
GIO.M224.TP	600 x 600 module	2 x 24W T5 G5	Output - 3500lms	Techno-Prismatic

Louvre

600 x 600 recessed office module only for central cross-blade louvre.

GIO.M155.LO	600 x 600 module	1 x 55W TC-L 2G11	Output - 4800lms	Cross-Blade Louvre
GIO.M224.LO	600 x 600 module	2 x 24W T5 G5	Output - 3500lms	Cross-Blade Louvre

55W : LOR= 79% 55°x 86°



Mod. + Tilt Spotlights



Prismatic


600 x 600 recessed office module with two recessed spot downlights in either 20W LED or 20W CDMT with central techno-prismatic fluxidrive™ diffuser [micro-prismatic].

GIO.TS155.TPL	600 x 600 module	1 x 55W TC-L 2G11	Spots- 2 x 20W LED	Techno-Prismatic
GIO.TS224.TPL	600 x 600 module	2 x 24W T5 G5	Spots -2 x 20W LED	Techno-Prismatic
GIO.TS155.TPC	600 x 600 module	1 x 55W TC-L 2G11	Spots- 2 x 20W CDM-T	Techno-Prismatic
GIO.TS224.TPC	600 x 600 module	2 x 24W T5 G5	Spots -2 x 20W CDM-T	Techno-Prismatic

Louvre

600 x 600 recessed office module with two recessed spot downlights in either 20W LED or 20W CDMT with central cross-blade louvre.

GIO.TS155.LOL	600 x 600 module	1 x 55W TC-L 2G11	Spots- 2 x 20W LED	Cross-Blade Louvre
GIO.TS224.LOL	600 x 600 module	2 x 24W T5 G5	Spots -2 x 20W LED	Cross-Blade Louvre
GIO.TS155.LOC	600 x 600 module	1 x 55W TC-L 2G11	Spots- 2 x 20W CDM-T	Cross-Blade Louvre
GIO.TS224.LOC	600 x 600 module	2 x 24W T5 G5	Spots -2 x 20W CDM-T	Cross-Blade Louvre



Mod. + EyeBall



Prismatic


600 x 600 recessed office module with two recessed adjustable drop down tilting downlights in 70W CDMT with central techno-prismatic fluxidrive™ diffuser [micro-prismatic].

GIO.EY155.TP	600 x 600 module	1 x 55W TC-L 2G11	Spots- 2 x 70W CDM-T	Techno-Prismatic
GIO.EY224.TP	600 x 600 module	2 x 24W T5 G5	Spots -2 x 70W CDM-T	Techno-Prismatic

Louvre

600 x 600 recessed office module with two recessed adjustable drop down tilting downlights in 70W CDMT with central cross-blade louvre

GIO.EY155.LO	600 x 600 module	1 x 55W TC-L 2G11	Spots- 2 x 70W CDM-T	Cross-Blade Louvre
GIO.EY224.LO	600 x 600 module	2 x 24W T5 G5	Spots -2 x 70W CDM-T	Cross-Blade Louvre



Module + Surface Spots



Prismatic


600 x 600 recessed module with two surface adjustable spotlights in 32W LED with central microprismatic fluxidrive™ diffuser.

GIO.SS155.TP	600 x 600 module	1 x 55W TC-L 2G11	Spots- 2 x 20W LED	Techno-Prismatic
GIO.SS224.TP	600 x 600 module	2 x 24W T5 G5	Spots -2 x 20W LED	Techno-Prismatic

Louvre

600 x 600 recessed module with two surface adjustable spotlights in 32W LED with central cross-blade louvre.

GIO.SS155.LO	600 x 600 module	1 x 55W TC-L 2G11	Spots- 2 x 20W LED	Cross-Blade Louvre
GIO.SS224.LO	600 x 600 module	2 x 24W T5 G5	Spots -2 x 20W LED	Cross-Blade Louvre



POST-FIX CODES


For codes with
DIMMING - HF gear defaults for HFR dimming by DALI ,DSI or 1-10V please add post-fix "-DALI", "-DSI" or "-1-10V" respectively. For more cost effective Compensated gear add post fix "-COMP".
PLASTER BOARD FIXINGS - For plaster-board fixing add post-fix "-PB".
EMERGENCY - 1 Hour or 3 Hour maintained please add post "-EM1" or "-EM3" respectively.
TPa>850°C Prismatic - For use of high thermal prismatic please add post-fix "TPA".

PERSCARA RX

monochromatic & RGB - circuit dimmable

LED Colour Consistency :
1 MacAdam Ellipse - 100K

IP65 IP20



Product Purpose & Meaning

- An advanced LED modules concept with "even" soft illumination using advanced anti-glare micro reflectors.
- Combined with CREE XPE reputable LED's.
- Perscara [Pur-scar-ra] is a derivative of the Italian - "Persino" meaning - "even" or uniform.

Product Summary

- "PRESCARA" is available as a dedicated LED fixture for interior offices, either for direct recessed 600x600 or as suspended direct / indirect 1000 x 596 module.
- Patented "Micro-Matt" 45° reflector technology for low glare comfort.
- 54 & 60 x 1.2W PowerLED's.
- Dimmable for use with remote PSU.

Applications

- Offices, Meeting rooms & Education buildings inc.class rooms.
- RGB Colour change adornment of spaces.

Performance

Lamp Type	1.2W PowerLED's.
LED Qty	Recessed 54 / Suspended 40+20
Lamp Source	CREE XPE
Lumen Output	54 / 60 x 120lms - White 5500K.
Lamp CRI	93 - White 3000K / 4000K.
LED Life	50,000hrs [CIE electronic parts default].
Optic Beams	Medium-Wide 45°.
LED Colours	Monochromatic Whites & RGB Tri-chip.
Working T°C	- 30°C / +85°C.

Electrical Data

Voltage	24Vdc.
Load Watts	65W & 72W units
Load Current	350mA.
Supply Cable	1.0M FROR 3 x 0.5mm² [RGB 5 x 0.5mm²].
Remote Gear	24Vdc Power Supply Unit [PSU].
Configuration	CV [Constant Voltage].
Dimming	Via a supplied 3rd dimming cable. Interface required.
Data Protocol(s)	Dimming Via:- Push-button [switch]. 0-10V analogue. DMX or DALI.

Description

A recessed square 600 x 600 modular with shallow recess depth to 80mm for lay in applications or a ceiling suspended module with 13mm blade profile. Both as a multiple PowerLED luminaires using "micro-matt" low glare patented white abs screen for special uniform glare-free high output light. Ideal for sustainable energy-efficient general office & retail illumination. Anti-dazzle low glare is suitable for PC screen use and modern office environments. Dimmable. Suspended version has 40 LED downlight and 20 LED indirect uplight array. Emergency versions. LED circuit board with extended life-saving thermal cut-out & output reduction with short circuit protection. Smooth easy-stay clean surface. RGB full colour option for, receptions, display areas and "relax" rest rooms.

Construction & Finishes

Extrusion and sheet manufacture. Chassis body in anodised aluminium Front screen in opal white ABS / PMMA acrylic.

Main Features

- "Micro-Matt" anti-dazzle technology.
- Remote PSU for direct 24V supply.
- 600 x 600 modularity.
- RGB full colour option.

Mounting

- Side arm brackets for lay-in ceilings. / Tensioned Clips for plasterboard type ceilings.
- Fine wire suspension for suspended type - standard 1.0m cable or mounting brackets for surface mounting.
- Supplied with 500mm length of H05RNF : 3-core 0.5mm² cable.

Connection Diagram J & K

- Connection is for bulk remote 24Vdc Power Supply [PSU].
- See Connection Diagram J & K - Page 329.
- See 24Vdc PSU's - Pages 330 - 332.


Standard Colours

- Warm White - 3000K - CRI = 93%
- Neutral White - 4000K - CRI = 93%
- Cool White - 5500K - CRI = 80%
- RGB Colour Change




units for DMX 512 Blending.

LED 230V ON SUSPENDED WITH HARNESS



PERSCARA XS

monochromatic & RGB - circuit dimmable




Product Order Codes




Perscara RX 600 x 600 Recessed Layin Module IP20

Recessed square module with 54 x 1.2W PowerLED's c/w micro-matt abs screen and distribution to 45°.

• PES.RX3	CRI = 93 -Warm	White 3000K	65W - 3,888lms	Med.Wide 45°
• PES.RX4	CRI = 93 -Int.	White 4000K	65W - 3,888lms	Med.Wide 45°
• PES.RX5	CRI = 80 -Cool	White 5500K	65W - 5400lms	Med.Wide 45°
• PES.XRGB	DMX 512	RGB	65W	Med.Wide 45°



45°	Ø-m	3000K-4000K	5500K
0,5	0,44	11250	17590
1	0,88	5345	9120
2	1,66	2370	3875
3	2,54	1020	2150



Perscara XS Ceiling Suspended Module IP65


Suspended module with 40 x 1.2W downlights & 20 x 1.2W PowerLED indirect uplights c/w micro-matt opal white pmma acrylic screen and distribution to 120°.

• PES.XS3	CRI = 93 -Warm	White 3000K	72W - 5,184lms	Wide 120°
• PES.XS4	CRI = 93 -Int.	White 4000K	72W - 5,184lms	Wide 120°
• PES.XS5	CRI = 80 -Cool	White 5500K	72W - 7,200lms	Wide 120°
• PES.XSRGB	DMX 512	RGB	90W	Wide 120°



120°	Ø-m	3000K-4000K	5500K
0,5	1,40	3970	5860
1	2,88	1420	2245
2	5,74	480	789
3	9,02	241	389

Accessories



230V Ceiling Plate

A ceiling plate housing & 230V termination for the suspended version. Designed as a matt white rectangular housing to take the wire suspension and gear.

PES.CP60	Ceiling Plate 230V	For 1 .0M & 2.0M	Mono White	24V PSU 60Va
PES.CP100	Ceiling Plate 230V	For 3.0M	Mono White	24V PSU 100Va
PES.CPRGB	Ceiling Plate 230V	Housing c/w	c/w DMX Interface	24V PSU 100Va

Pre-Connected Remote Boxed Gear [individual]

A Remote Box for quick connect housing c/w integral individual gear for 230V connection. Designed for hiding in close proximity of ceiling voids. One per individual fitting.

PES.RB60	Remote Box 230V	For 1 .0M & 2.0M	Mono White	24V PSU 60Va
PES.RB100	Remote Box 230V	For 3.0M	Mono White	24V PSU 100Va
PES.RBRGB	Remote Box 230V	For all RGB	c/w DMX Interface	24V PSU 100Va

OFFICE MODULES SUSPENDED & SYSTEMS

product pages start page 27

office - retail - leisure

OFFICE MODULES SUSPENDED & SYSTEMS

office - retail - leisure

product pages start page 27

6

7

RECESSED MODULES

T5 - 2x54W Page 28
1200x300



techno-micro-prismatics

OFFICIO series

T5 - 2x24W Page 28
600x600



OFFICIO series

T5 - 2x24W Page 28
600x600



OFFICIO series

Page 30



RETAIL STORE

LED - 65W Page 34
600x600



PERSCARA RX

T5 - 2x24W Page 32
600x600



GIOTTO XS series

T5 - 2x24W Page 32
600x600



GIOTTO XS series

T5 - 2x24W Page 32
600x600



GIOTTO XS series

SUSPENDED SYSTEM

SYSTEM Page 57



XICATA 48 series - T5

SYSTEM Page 57/61




XICATA 48 - T5 & SPOTS

SYSTEM Page 61



XICATA 48 series - SPOTS

SYSTEM Page 65



XICATA 48 - SINGLE T5

SYSTEM Page 67



XICATA 48 - ROTATOR 1

SYSTEM Page 71



XICATA 48 - WALL UNITS

SYSTEM Page 69



XICATA 48 - VIENNA

SYSTEM Page 69



XICATA 48 - TUBE

SYSTEM Page 69




XICATA 48 - LED SPOTS

SYSTEM Page 67



XICATA 48 - ROTATOR 2



HAIR SALONS



LIBRARY'S




CAR DEALERSHIPS



RETAIL



SCHOOLS



RECEPTIONS

SUSPENDED LUMINAIRES

Page 36 30x3W - LED



MONZA

Page 38 3x54W - T5



VERONA

Page 40 3x80W - T5



AILERON

Page 42 LED - 32x3W



CHIARO

Page 44 LED - 32x3W



LATLUCE

Page 46 2x54W - T5



MILANO series

Page 46 2x54W - T5




MILANO series

Page 48 2x24W - T5



VIENNA

Page 35 LED - 72W



PERSCARA XS

Page 103 LED - 20W/m



AMBIENTALE

Page 26



OFFICE'S

Page 46



OFFICE'S

Page 39



OFFICE'S

SURFACE

Page 48 2x80W - T5



VIENNA

Page 48



OFFICE'S

RECESSED SYSTEM

Page 50 SYSTEM




XICATA 77 RECESSED

Page 51 SYSTEM



XICATA 77 RECESSED

Page 54



OFFICE'S

OFFICE WALL LUMINAIRES

Page 228 2x55W TC-1



ASYAERO

Page 229 1x55W TC-1



KEELIO



DEALER ROOMS